



HEIN | LEHMANN

CONIDUR®

**PRODUCTION AREA CONIDUR®-
SLOTTED HOLE SHEETS**

PRODUCTION AREA CONIDUR® SLOTTED HOLE SHEETS

MILD STEEL

Initial sheet thickness	CONIDUR®-slotted hole		Standard production width	
	min.	max.	uncut	rectangular
mm	mm	mm	mm	mm
0.50	0.06 x 2	0.20 x 2	650	600
	0.10 – 0.12 x 3	0.80 x 3	810	750
	0.12 – 0.13 x 4	0.80 x 4	810	750
0.75	0.20 x 3	0.80 x 3	650	600
	0.20 x 4	1.00 x 4	650	600
1.00	0.25 x 3	0.60 x 3	800	750
	0.20 x 4	1.00 x 4	800	750
1.25	0.25 x 4	1.00 x 4	650	600

In order to achieve a larger open area, we have developed slotted hole on the basis of fine holes.

The slot length is always parallel to the production width.

PRODUCTION AREA CONIDUR® SLOTTED HOLE SHEETS

STAINLESS STEEL

Initial sheet thickness	CONIDUR®-slotted hole		Standard production width	
	min.	max.	uncut	rectangular
mm	mm	mm	mm	mm
0.20 / 0.25	0.05 x 1.0	0.15 x 1.0	550	500
	0.05 x 2.0	0.15 x 2.0	550	500
0.20 / 0.35	0.05 x 2.0	0.30 x 2.0	610	550
	0.05 x 2.5	0.30 x 2.5	610	550
0.25 / 0.35	0.06 x 2.0	0.20 x 2.0	610	550
	0.08 x 3.0	0.30 x 3.0	610	530
	0.13 x 4.0	0.35 x 4.0	610	530
0.50	0.08 x 2.0	0.20 x 2.0	610	580
	0.12 x 3.0	0.50 x 3.0	610	580
	0.15 x 4.0	0.60 x 4.0	610	580
0.70	0.20 x 3.0	0.80 x 3.0	610	580
	0.20 x 4.0	0.90 x 4.0	610	580
1.00	0.20 x 4.0	0.90 x 4.0	660	620

In order to achieve a larger open area, we have developed slotted hole on the basis of fine holes.

The slot length is always parallel to the production width.